

Specifications

Product	
Weight	12 Lbs
Environment	
Certified Ambient Temperature	0 to 40 °C [32 to 104 °F]
Functional Ambient Temperature	-50 to 85 °C [-58 to 185 °F]
Enclosure Material	319 cast aluminum
Enclosure Rating (UL)	NEMA Type 1, 3, 3R, 4, 4X
Enclosure Rating (CSA)	NEMA Type 3, 4, 4X
Mounting	3 10mm mounting holes
Switch	
Switch Type	SPDT (sub model dependant)
Contact Type	Dry Contact
Contact Rating (UL)	20A @ 125V, 250V or 480V AC; 1 hp @ 125V AC; 2 hp @ 250V AC
Contact Rating (CSA)	20A @ 125V, 250V or 480V AC; 1 hp @ 125V AC; 2 hp @ 250V AC; ½ A @ 125V DC; ¼ A @ 250V DC
Electrical Action	Latching (via actuator)
Electrical Connection	¾" NPT x 3
Actuator	
Cable Length	100 feet on each side
Cable Material	galvanized aircraft cable

Product Certification

Standard	Class	Division	Group(s)
UL 508	N/A	N/A	N/A
CSA 3211-06	N/A	N/A	N/A



Ordering

Model Number	Part Number
Model RS	800-003200

*For other part numbers please contact Sales Dept.

Complete System Includes

- Safety Switch
- 10ft of cable (per unit)

Options and Accessories

Option	Picture
Orange nylon coated Cable	
Orange vinyl coated cable	
Mounting Bracket	
Cable Support Eyebolt, 1/2" x 6" Plated	
Cable End Fitting/ Cable Clamp (each)	

Common Applications

- Conveyors
- Production Lines
- Assembly Lines
- Material Handling

Typical Industries

- Grain
- Manufacturing
- Mining
- Construction
- Assembly Lines